

MATERIAL SAFETY DATASHEET

PLAKA – ANKROCHIM SF3000 Part A

Chemical Anchor REF 06.01.31 - Version V02 - 22/12/2020



ΡΙΛΚΛ

Ankrochim SF3000 Part A

Content revision date 25/07/2018 According to Regulation (EC) No 1907/2006, Annex II, as amended

SECTION 1: Identification of	the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Ankrochim SF3000 Part A
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Identified uses	Two-component, epoxy-based adhesive. Resin.
1.3. Details of the supplier of	f the safety data sheet
Supplier	Leviat
	Industrielaan 2
	B-1740 Ternat
	Belgium
	T : +32 (0)2 582 29 45
	F : +32 (0)2 582 19 62
	info.plaka.be@leviat.com
	Plaka-Solutions.com
1.4. Emergency telephone n	umber
Emergency telephone	+32 (0)2 582 29 45 (08:00 - 17:00)
SECTION 2: Hazards identif	ication
2.1. Classification of the sub	stance or mixture
Classification (EC 1272/2008	8)
Physical hazards	Not Classified
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards	Aquatic Chronic 2 - H411
2.2. Label elements	
Hazard pictograms	
Signal word	Warning
Hazard statements	H315 Causes skin irritation.
	H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

©Copyright protected

This sheet, written with great care, supersedes all previous versions. The technical information on the design, models, illustrations, design values and specifications are believed to be accurate. We make no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with non suitable use of this product. We reserve the right to modify the contents of this form without prior notice.

For further information, please contact your Leviat office. Belgium : <u>info.plaka.be@leviat.com</u> / + 32 (0) 2 582 29 45 France : <u>info.plaka.fr@leviat.com</u> / +33 (0) 5 34 25 54 82

Precautionary statements	 P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
Contains	reaction product: bisphenol-A-(epichlorhydrin), EPOXY PHENOL FORMALDEHYDE RESIN, REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYL)OXIRANE(1:2)
Supplementary precautionary statements	 P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage.

2.3. Other hazards

3.2. Mixtures

EPOXY RESIN (Number average	∋ MW <= 700)	20-50%
CAS number: 25068-38-6	EC number: 500-033-5	
Classification		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		
EPOXY PHENOL FORMALDEH	YDE RESIN	10-20%
CAS number: 9003-36-5	EC number: 500-006-8	REACH registration number: 01-
		2119454392-40
Classification		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		

REACTION PRODUCTS OF CHLOROMETHYL)OXIRANE		5-10%
CAS number: 933999-84-9	EC number: 618-939-5	REACH registration number: 01- 2119463471-41
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1A - H317 Aquatic Chronic 3 - H412		
The Full Text for all R-Phrases	s and Hazard Statements are Displayed in S	ection 16.
Composition comments	CAS 9003-36-5 = CAS 20864-14-4 (RoW)	CAS 933999-84-9 = CAS 16096-31-4 (RoW)
SECTION 4: First aid measure	98	
4.1. Description of first aid mea	asures	
Inhalation	Remove affected person from source of co continues.	ontamination. Get medical attention if any discomfo
Ingestion	Do not induce vomiting. Get medical attent	tion immediately.
Skin contact	Remove contaminated clothing immediatel	ly and wash skin with soap and water.
Eye contact		emove any contact lenses and open eyelids wide utes. Get medical attention if irritation persists after he medical personnel.
4.2. Most important symptoms	and effects, both acute and delayed	
nhalation	May cause respiratory irritation.	
Ingestion	May cause stomach pain or vomiting.	
Skin contact	Prolonged or repeated contact with skin ma cause sensitisation by skin contact.	ay cause irritation, redness and dermatitis. May
Eye contact	Irritating to eyes.	
4.3. Indication of any immedia	te medical attention and special treatment ne	eeded
Notes for the doctor	No specific recommendations. If in doubt, g	get medical attention promptly.
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with alcohol-resistant foam, carl	bon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water, if avoidable.	
5.2. Special hazards arising fro	om the substance or mixture	
Specific hazards	Not considered to be a significant hazard of	due to the small quantities used.
Hazardous combustion products	Oxides of carbon. Oxides of nitrogen.	
5.3. Advice for firefighters		
Protective actions during firefighting	No specific requirements are anticipated un	nder normal conditions of use.

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
SECTION 6: Accidental release measures	
6.1. Personal precautions, pro	tective equipment and emergency procedures
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
6.2. Environmental precaution	<u>S</u>
Environmental precautions	Avoid release to the environment.
6.3. Methods and material for containment and cleaning up	
Methods for cleaning up	Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.
6.4. Reference to other section	ns
Reference to other sections	For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13.
SECTION 7: Handling and sto	rage
7.1. Precautions for safe hand	ling
Usage precautions	Avoid contact with eyes. Avoid contact with skin.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
7.2. Conditions for safe storag	e, including any incompatibilities
Storage precautions	Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
SECTION 8: Exposure control	s/Personal protection
8.1. Control parameters	
	EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)
DNEL	Industry - Inhalation; Long term systemic effects: 12.25 mg/m ³ Industry - Inhalation; Short term systemic effects: 12.25 mg/m ³ Industry - Dermal; Long term systemic effects: 8.33 mg/kg/day Industry - Dermal; Short term systemic effects: 8.33 mg/kg/day REACH dossier information
PNEC	 Fresh water; 0.006 mg/l marine water; 0.0006 mg/l Intermittent release; 0.018 mg/l STP; 10 mg/l Sediment (Freshwater); 0.996 mg/kg Sediment (Marinewater); 0.0996 mg/kg Soil; 0.196 mg/kg REACH dossier information

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYL)OXIRANE(1:2) (CAS: 933999-84-9)

DNEL	Industry - Inhalation; Long term systemic effects: 4.9 mg/m ³ Industry - Inhalation; Short term systemic effects: 4.9 mg/m ³ Industry - Inhalation; Long term local effects: 0.44 mg/m ³ Industry - Dermal; Long term systemic effects: 2.8 mg/kg/day Industry - Dermal; Long term local effects: 22.6 µg/cm ² Industry - Dermal; Short term local effects: 22.6 µg/cm ² REACH dossier information
PNEC	 Fresh water; 0.0115 mg/l marine water; 0.00115 mg/l Intermittent release; 0.115 mg/l STP; 1 mg/l Sediment (Freshwater); 0.283 mg/kg Sediment (Marinewater); 0.0283 mg/kg Soil; 0.223 mg/kg REACH dossier information

8.2. Exposure controls

Protective equipment





Appropriate engineering controls	No specific ventilation requirements.
Eye/face protection	Wear eye protection.
Hand protection	Wear protective gloves made of the following material: Nitrile rubber.
Hygiene measures	Provide eyewash station. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.
Respiratory protection	Not relevant.
Environmental exposure controls	Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

Appearance	Liquid.
Colour	Pink.
Odour	Characteristic.
Odour threshold	Not determined.
рН	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	>35°C @ 760 mm Hg
Flash point	>100°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	Not applicable.

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	Not available.
Vapour pressure	<500 Pa @ °C
Vapour density	No information available.
Relative density	1.5 - 1.6
Bulk density	Not applicable.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	> 60 S ISO2431
Explosive properties	No information available.
Explosive under the influence of a flame	No
Oxidising properties	Does not meet the criteria for classification as oxidising.
9.2. Other information	
OFOTION 40. Otability and rea	and the second
SECTION 10: Stability and rea	
10.1. Reactivity	
	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols.
10.1. Reactivity	
10.1. Reactivity Reactivity	
10.1. Reactivity Reactivity 10.2. Chemical stability	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended.
10.1. Reactivity Reactivity 10.2. Chemical stability Stability	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended.
10.1. ReactivityReactivity10.2. Chemical stabilityStability10.3. Possibility of hazardousPossibility of hazardous	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended.
10.1. ReactivityReactivity10.2. Chemical stabilityStability10.3. Possibility of hazardousPossibility of hazardousreactions	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended.
10.1. ReactivityReactivity10.2. Chemical stabilityStability10.3. Possibility of hazardousPossibility of hazardousreactions10.4. Conditions to avoid	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended. reactions The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols.
10.1. ReactivityReactivity10.2. Chemical stabilityStability10.3. Possibility of hazardousPossibility of hazardousreactions10.4. Conditions to avoidConditions to avoid	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended. reactions The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols.
10.1. ReactivityReactivity10.2. Chemical stability10.2. Chemical stabilityStability10.3. Possibility of hazardousPossibility of hazardousreactions10.4. Conditions to avoidConditions to avoid10.5. Incompatible materials	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended. reactions The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Avoid contact with acids and alkalis. Acids. Amines. Amides.
10.1. ReactivityReactivity10.2. Chemical stability10.2. Chemical stabilityStability10.3. Possibility of hazardousPossibility of hazardousreactions10.4. Conditions to avoidConditions to avoid10.5. Incompatible materialsMaterials to avoid	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended. reactions The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Avoid contact with acids and alkalis. Acids. Amines. Amides.
10.1. Reactivity Reactivity 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous reactions 10.4. Conditions to avoid Conditions to avoid 10.5. Incompatible materials Materials to avoid 10.6. Hazardous decomposition	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended. reactions The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Avoid contact with acids and alkalis. Acids. Amines. Amides. <u>m products</u> Oxides of carbon. Oxides of nitrogen.
10.1. Reactivity Reactivity 10.2. Chemical stability 10.2. Chemical stability Stability 10.3. Possibility of hazardous Possibility of hazardous reactions 10.4. Conditions to avoid Conditions to avoid 10.5. Incompatible materials Materials to avoid 10.6. Hazardous decomposition products	The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Stable at normal ambient temperatures and when used as recommended. reactions The following materials may react with the product: Acids. Amides. Amines. Phenols, cresols. Avoid contact with acids and alkalis. Acids. Amines. Amides. n products Oxides of carbon. Oxides of nitrogen.

General information	Contains epoxy constituents. May produce an allergic reaction.
Inhalation	No specific health hazards known.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Irritating to skin. May cause sensitisation by skin contact.
Eye contact	May cause severe eye irritation.
Acute and chronic health hazards	Irritating to skin. Irritating to eyes.
Route of exposure	Skin and/or eye contact
Medical symptoms	Skin irritation.
Medical considerations	Skin disorders and allergies.
Toxicological information on ingredients.	
REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYL)OXIRANE(1:2)	
Acute toxicity - oral	

 Acute toxicity oral (LD₅₀ mg/kg)	3,010.0
Species	Rat
SECTION 12: Ecological information	

12.1. Toxicity

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute aquatic toxicity	
Acute toxicity - fish	LC50, 96 hours: 2 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: 1.8 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC₅₀, 72 hours: 11 mg/l, Freshwater algae EC₅₀, 96 hours: 220 mg/l, Scenedesmus subspicatus
Chronic aquatic toxicity	
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 0.3 mg/l, Daphnia magna

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYL)OXIRANE(1:2)

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 30 mg/l, Oncorhynchus mykiss (Rainbow trout)

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Biodegradation

- 12% Degradation (%): 28 days

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYL)OXIRANE(1:2)

	Biodegradation		- 47% Degradation (%): 28 days OECD 301D
12.3. Bioacc	umulative potentia	al	
Bioaccumula	ative potential	No data	available on bioaccumulation.
Partition coe	efficient	Not determined.	
Ecological in	nformation on ingre	edients.	
			EPOXY RESIN (Number average MW <= 700)
	Bioaccumulative	potential	May accumulate in soil and water systems. BCF: 100 - 3000,
	Partition coefficie	ent	log Pow: 3.242 Estimated Value
	REAC	TION PRO	DUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYL)OXIRANE(1:2)
	Bioaccumulative	potential	BCF: < 100, Estimated Value
	Partition coefficie	ent	log Pow: -0.272 Estimated Value
12.4. Mobilit	y in soil		
Mobility		-	luct is insoluble in water and will spread on the water surface. The product is non- Semi-mobile.
Ecological in	nformation on ingre	edients.	
			EPOXY RESIN (Number average MW <= 700)
	Mobility		Semi-mobile.
	Adsorption/desor coefficient	rption	Water - Koc: 1800 - 4400 @ 25°C Estimated Value
	Henry's law cons	stant	4.93E-05 Pa m3/mol @ 25°C
12.5. Result	s of PBT and vPvI	B assessm	lent
Results of P assessment	BT and vPvB	This proc	duct does not contain any substances classified as PBT or vPvB.
Ecological in	nformation on ingre	edients.	
			EPOXY RESIN (Number average MW <= 700)
	Results of PBT a assessment	Ind vPvB	This substance is not classified as PBT or vPvB according to current EU criteria.
12.6. Other a	adverse effects		
SECTION 1	3: Disposal consid	lerations	
13.1. Waste	treatment method	ls	
Disposal me	thods		s and empty containers should be taken care of as hazardous waste according to I national provisions. Dispose of waste via a licensed waste disposal contractor.
Waste class		The was (EWC).	te code classification is to be carried out according to the European Waste Catalogue

SECTION 14: Transport information

14.1. UN number	
UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082
14.2. UN proper shipping name	
Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW <= 700), EPOXY PHENOL FORMALDEHYDE RESIN)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW <= 700), EPOXY PHENOL FORMALDEHYDE RESIN)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW <= 700), EPOXY PHENOL FORMALDEHYDE RESIN)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (Number average MW <= 700), EPOXY PHENOL FORMALDEHYDE RESIN)
14.3. Transport hazard class(e	s)
ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9
Transport labels	

14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



 $\underline{\textbf{14.6. Special precautions for user}}$

EmS

F-A, S-F 3

ADR transport category

Emergency Action Code •3Z

Hazard Identification Number 90 (ADR/RID)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

EU legislation (EU) No 2015/830

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	25/07/2018
Version number	1.000
SDS number	21176
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



MATERIAL SAFETY DATASHEET

PLAKA – ANKROCHIM SF3000 Part B

Chemical Anchor REF 06.01.31 - Version V02 - 22/12/2020



ΡLΛΚΛ

Ankrochim SF3000 Part B

Content revision date 03/09/2019 According to Regulation (EC) No 1907/2006, Annex II, as amended

SECTION 1: Identification of	SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier			
Product name	Ankrochim SF3000 Part B		
1.2. Relevant identified uses of the substance or mixture and uses advised against			
Identified uses	Two-component, epoxy-based adhesive. Hardener.		
1.3. Details of the supplier of	1.3. Details of the supplier of the safety data sheet		
Supplier	Leviat		
	Industrielaan 2		
	B-1740 Ternat		
	Belgium		
	T : +32 (0)2 582 29 45		
	F : +32 (0)2 582 19 62		
Web	info.plaka.be@leviat.com		
Contact person	Plaka-Solutions.com		
1.4. Emergency telephone nu	mber		
Emergency telephone	+32 (0)2 582 29 45 (08:00 - 17:00)		
SECTION 2: Hazards identification			
2.1. Classification of the subs	tance or mixture		
Classification (EC 1272/2008	-		
Physical hazards			
	Not Classified		
Health hazards	Not Classified Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317		
Health hazards Environmental hazards			
Environmental hazards	Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412		
Environmental hazards Human health	Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412 Corrosive. Prolonged contact causes serious eye and tissue damage.		
Environmental hazards Human health Environmental	Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412		
Environmental hazards Human health Environmental 2.2. Label elements	Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412 Corrosive. Prolonged contact causes serious eye and tissue damage.		
Environmental hazards Human health Environmental	Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412 Corrosive. Prolonged contact causes serious eye and tissue damage.		
Environmental hazards Human health Environmental 2.2. Label elements	Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412 Corrosive. Prolonged contact causes serious eye and tissue damage.		

©Copyright protected

This sheet, written with great care, supersedes all previous versions. The technical information on the design, models, illustrations, design values and specifications are believed to be accurate. We make no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with non suitable use of this product. We reserve the right to modify the contents of this form without prior notice.

PLAKA-SOLUTIONS.COM

For further information, please contact your Leviat office. Belgium : <u>info.plaka.be@leviat.com</u> / + 32 (0) 2 582 29 45 France : <u>info.plaka.fr@leviat.com</u> / +33 (0) 5 34 25 54 82

Hazard statements	H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	 P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/ container in accordance with national regulations.
Contains	1,3-CYCLOHEXANEBIS(METHYLAMINE), STYRENATED PHENOL, SALICYLIC ACID, 1,3- BENZENEDIMETHANAMINE
Supplementary precautionary statements	 P264 Wash contaminated skin thoroughly after handling. P260 Do not breathe vapours. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up.

SECTION 3: Composition/informa 3.2. Mixtures		
1,3-CYCLOHEXANEBIS(METHY	(LAMINE)	20-509
CAS number: 2579-20-6	EC number: 219-941-5	REACH registration number: 01- 2119543741-41
Classification		
Acute Tox. 4 - H302		
Acute Tox. 4 - H312		
Skin Corr. 1A - H314		
Aquatic Chronic 3 - H412		
STYRENATED PHENOL		5-109
CAS number: 61788-44-1	EC number: 262-975-0	REACH registration number: 01-
		2119979575-18
Classification		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Skin Sens. 1A - H317		

SALICYLIC ACID			5-10%
CAS number: 69-72-7	EC number: 200-712-3	REACH registration number: 01- 2119486984-17	
Classification			
Acute Tox. 4 - H302			
Eye Dam. 1 - H318			
1,3-BENZENEDIMETHANAMINE			1-5%
CAS number: 1477-55-0	EC number: 216-032-5		
Classification			
Acute Tox. 4 - H302			
Acute Tox. 4 - H332			
Skin Corr. 1B - H314			
Skin Sens. 1B - H317			
Aquatic Chronic 3 - H412			
The Full Text for all R-Phrases and Haza	rd Statements are Displayed in Section 16).	
SECTION 4: First aid measures			
4.1. Description of first aid measures			

Inhalation	Remove affected person from source of contamination. Get medical attention if any discomfort continues.		
Ingestion	Do not induce vomiting. Get medical attention immediately.		
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.		
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.		
4.2. Most important symptoms	and effects, both acute and delayed		
Inhalation	Irritation of nose, throat and airway.		
Ingestion	May cause stomach pain or vomiting.		
Skin contact	Burning pain and severe corrosive skin damage. Blistering may occur. Chemical burns.		
Eye contact	May cause blurred vision and serious eye damage.		
4.3. Indication of any immedia	4.3. Indication of any immediate medical attention and special treatment needed		
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.		
SECTION 5: Firefighting meas	sures		
5.1. Extinguishing media			
Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.		
Unsuitable extinguishing media	Do not use water, if avoidable.		
5.2. Special hazards arising fr	om the substance or mixture		

Specific hazards

No specific firefighting precautions applicable when small quantities are involved in the fire.

Hazardous combustion	Oxides of carbon. Oxides of nitrogen.
•	
5.3. Advice for firefighters	No apositio firefishting processions known
Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
SECTION 6: Accidental releas	e measures
6.1. Personal precautions, pro	tective equipment and emergency procedures
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
6.2. Environmental precaution	S
Environmental precautions	Collect and dispose of spillage as indicated in Section 13. Contain spillage with sand, earth or other suitable non-combustible material. Avoid discharge into drains or watercourses or onto the ground.
6.3. Methods and material for	containment and cleaning up
Methods for cleaning up	Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.
6.4. Reference to other section	าร
Reference to other sections	For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13.
SECTION 7: Handling and sto	rage
7.1. Precautions for safe hand	ling
Usage precautions	Avoid contact with skin. Avoid contact with eyes. Do not empty into drains.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
7.2. Conditions for safe storag	e, including any incompatibilities
Storage precautions	Keep away from food and drink. Keep container tightly sealed when not in use.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
SECTION 8: Exposure control	s/Personal protection
8.1. Control parameters	
Occupational exposure limits	
1,3-CYCLOHEXANEBIS(MET	HYLAMINE)
Long-term exposure limit (8-hour TWA): WEL 0.1 ppm(Sk) 0.8 mg/m3(Sk) Sk WEL = Workplace Exposure Limit	

WEL = Workplace Exposure Limit Sk = Can be absorbed through skin.

1,3-CYCLOHEXANEBIS(METHYLAMINE) (CAS: 2579-20-6)

DNEL	REACH dossier information Industry - Inhalation; Long term systemic effects: 0.71 mg/m ³ Industry - Dermal; Short term systemic effects: 6 mg/kg/day Industry - Inhalation; Short term systemic effects: 21.2 mg/m ³ Industry - Dermal; Long term systemic effects: 0.2 mg/kg/day
PNEC	REACH dossier information - marine water; 0.00331 mg/l - Fresh water; 0.0331 mg/l - Intermittent release; 0.331 mg/l - STP; 10 mg/l
	STYRENATED PHENOL (CAS: 61788-44-1)
DNEL	REACH dossier information Industry - Inhalation; Long term systemic effects: 0.734649123 mg/m³ Industry - Dermal; Long term systemic effects: 0.4166666667 mg/kg/day
PNEC	REACH dossier information - Sediment (Marinewater); 43.65269484 mg/kg - Soil; 20.64517608 mg/kg - marine water; 0.0001371 mg/l - Sediment (Freshwater); 43.65269484 mg/kg - Intermittent release; 0.01371 mg/l - STP; 1.0638 mg/l - Fresh water; 0.001371 mg/l
	SALICYLIC ACID (CAS: 69-72-7)
DNEL	REACH dossier information Industry - Inhalation; Long term systemic effects: 16 mg/m³ Industry - Dermal; Long term systemic effects: 2 mg/kg/day
PNEC	REACH dossier information - Sediment (Marinewater); 0.142 mg/kg - Intermittent release; 1 mg/l - Fresh water; 0.2 mg/l - Sediment (Freshwater); 1.42 mg/kg - STP; 162 mg/l - Soil; 0.166 mg/kg - marine water; 0.02 mg/l
	1,3-BENZENEDIMETHANAMINE (CAS: 1477-55-0)
PNEC	 Sediment (Marinewater); 0.043 mg/kg Intermittent release; 0.152 mg/l Soil; 0.045 mg/kg marine water; 0.0094 mg/l Sediment (Freshwater); 0.43 mg/kg STP; 10 mg/l Fresh water; 0.094 mg/l
8.2. Exposure controls	

Protective equipment





Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	The following protection should be worn: Tight-fitting safety glasses. Contact lenses should not be worn when working with this chemical.
Hand protection	Wear protective gloves made of the following material: Nitrile rubber.
Other skin and body protection	Avoid contact with skin. Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Use engineering controls to reduce air contamination to permissible exposure level.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.
Environmental exposure controls	Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic phys	ical and chemical properties
Appearance	Liquid.
Colour	Buff.
Odour	Characteristic. Amine.
Odour threshold	Not determined.
рН	Not applicable.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	>100°C Closed cup.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not applicable.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.4 - 1.5
Bulk density	Not available.
Solubility(ies)	Not determined.
Partition coefficient	Not determined.

Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	No information available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.
9.2. Other information	
SECTION 10: Stability and rea	ctivity
10.1. Reactivity	
Reactivity	The following materials may react with the product: Acids. Epoxides. Oxidising agents. Peroxides.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures and when used as recommended.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	The following materials may react with the product: Acids. Epoxides. Oxidising agents. Peroxides.
10.4. Conditions to avoid	
Conditions to avoid	No specific requirements are anticipated under normal conditions of use.
10.5. Incompatible materials	
Materials to avoid	Acids. Epoxides. Oxidising agents. Peroxides.
10.6. Hazardous decompositio	n products
Hazardous decomposition products	Oxides of carbon. Oxides of nitrogen.
SECTION 11: Toxicological inf	ormation
11.1. Information on toxicologi	cal effects
Acute toxicity - oral	
ATE oral (mg/kg)	1,244.54
Acute toxicity - dermal ATE dermal (mg/kg)	3,234.71
Acute toxicity - inhalation ATE inhalation (dusts/mists mg/l)	58.23
Skin sensitisation Skin sensitisation	Sensitising.
Inhalation	Vapour may irritate respiratory system/lungs.
Ingestion	May cause stomach pain or vomiting.
Skin contact	May cause sensitisation by skin contact. May cause serious chemical burns to the skin.

Eye contact	Risk of serious damage to eyes. May cause chemical eye burns.
Acute and chronic health hazards	May cause sensitisation by skin contact. Causes severe burns.
Route of exposure	Skin and/or eye contact Inhalation
Target organs	No specific target organs known.
Medical symptoms	Symptoms following overexposure may include the following: Chemical burns.

Toxicological information on ingredients.

1,3-CYCLOHEXANEBIS(METHYLAMINE)

Acute toxicity - oral		
Acute toxicity oral (LD₅₀ mg/kg)	700.0	
Species	Rat	
Acute toxicity - dermal		
Acute toxicity dermal (LD₅ mg/kg)	1,700.0	
Species	Rabbit	
		STYRENATED PHENOL
Acute toxicity - oral		
Acute toxicity oral (LD₅₀ mg/kg)	2,000.0	
Species	Rat	
Acute toxicity - dermal		
Acute toxicity dermal (LD∞ mg/kg)	2,000.0	
Species	Rat	
		SALICYLIC ACID
Acute toxicity - oral		
Acute toxicity oral (LD₅₀ mg/kg)	891.0	
Species	Rat	
Acute toxicity - dermal		
Acute toxicity dermal (LD∞ mg/kg)	2,000.0	
Species	Rat	
		1,3-BENZENEDIMETHANAMINE
Acute toxicity - oral		
Acute toxicity oral (LD₅o mg/kg)	1,090.0	

Species	Rat
ATE oral (mg/kg)	1,090.0
Acute toxicity - dermal	
Acute toxicity dermal (LD∞ mg/kg)	2,000.0
Species	Rat
Acute toxicity - inhalation	
Acute toxicity inhalation (LC _∞ dust/mist mg/l)	1.34
Species	Rat
ATE inhalation (dusts/mists mg/l)	1.34

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

microorganisms

1,3-CYCLOHEXANEBIS(METHYLAMINE)

Acute aquatic toxicity	
Acute toxicity - fish	LC50, > 96 hours: 100 mg/l, Leuciscus idus (Golden orfe)
Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: 29 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC_{50} , > 96 hours: 100 mg/l, Scenedesmus subspicatus
Acute toxicity - terrestrial	EC₅₀, > 14 days: 1000 mg/kg, Eisenia Fetida (Earthworm)
	STYRENATED PHENOL
Acute aquatic toxicity	
Acute toxicity - fish	LC50, 96 hours: 14.8 mg/l,
Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: 1-10 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 3.14 mg/l, Scenedesmus subspicatus
Chronic aquatic toxicity	
NOEC	$0.01 \leq \text{NOEC} \leq 0.1$
	SALICYLIC ACID
Acute aquatic toxicity	
Acute toxicity - fish	LC50, 48 hours: 90 mg/l, Leuciscus idus (Golden orfe)
Acute toxicity -	EC₅₀, > 3 hours: 3200 mg/l, Activated sludge

9/12

1,3-BENZENEDIMETHANAMINE

Acute	aquatic toxicity		
Acute	e toxicity - fish	LC50, 96 hours: 75 mg/l, Leuciscus idus (Golden orfe)	
	e toxicity - aquatic tebrates	EC₅₀, 48 hours: 15.2 mg/l, Daphnia magna	
Acute plant	e toxicity - aquatic s	EC₅₀, 72 hours: 12 mg/l, Scenedesmus subspicatus	
12.2. Persistence	and degradability		
Persistence and de	egradability There a	are no data on the degradability of this product.	
12.3. Bioaccumula	tive potential		
Bioaccumulative p	otential No data	a available on bioaccumulation.	
Partition coefficien	t Not det	termined.	
12.4. Mobility in sc	bil		
Mobility	Mobile.	The product is miscible with water and may spread in water systems.	
12.5. Results of PBT and vPvB assessment			
Results of PBT an assessment	d vPvB This pr	This product does not contain any substances classified as PBT or vPvB.	
12.6. Other advers	e effects		
SECTION 13: Disp	oosal considerations		
13.1. Waste treatn	nent methods		
General informatio		Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.	
Disposal methods	Dispos	Dispose of waste via a licensed waste disposal contractor.	
Waste class	The wa (EWC).	aste code classification is to be carried out according to the European Waste Catalogue	
SECTION 14: Tran	nsport information		
14.1. UN number			
UN No. (ADR/RID)	2735		
UN No. (IMDG)	2735		
UN No. (ICAO)	2735	2735	
UN No. (ADN)	2735	2735	
14.2. UN proper st	nipping name		
Proper shipping na (ADR/RID)		S, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3- DHEXANEBIS(METHYLAMINE), 1,3-BENZENEDIMETHANAMINE)	
Proper shipping na	· ·	S, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3- DHEXANEBIS(METHYLAMINE), 1,3-BENZENEDIMETHANAMINE)	
Proper shipping na	· ·	S, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3- DHEXANEBIS(METHYLAMINE), 1,3-BENZENEDIMETHANAMINE)	

Proper shipping name (ADN)	AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 1,3-
	CYCLOHEXANEBIS(METHYLAMINE), 1,3-BENZENEDIMETHANAMINE)

14.3.	Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C7
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

Transport labels



14.4. Packing group		
ADR/RID packing group	П	
IMDG packing group	П	
ICAO packing group	II	
ADN packing group	П	

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

IMDG Code segregation group	18. Alkalis
EmS	F-A, S-B
ADR transport category	2
Emergency Action Code	2X
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EU) No 2015/830

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information		
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.	
Revision date	03/09/2019	
Version number	3.001	
Supersedes date	16/11/2018	
SDS number	21177	
Hazard statements in full	 H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. 	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.